ONTAROAGRA

Subdrain/Weeping Tile

Drainage tile rolls come in a variety of sizes. They can be perforated, solid or in filter cloth. Single wall corrugated HDPE pipe is ideal for drainage projects where flexibility, lightweight and low cost are important.

Single wall corrugated pipe has kept farms, golf courses, parks and playing fields dry for decades by channelling away excess underground moisture. Homeowners find that the single wall HDPE corrugated pipe is an economical, easy-to-install solution to common residential stormwater drainage problems. These may include downspouts runoff, foundation and window well drains, driveway culverts and wet spots on the lawn. Single wall HDPE pipe is also used for highway edge drains, culverts and other construction applications where economy and durability are a priority.

Sizing Chart

Size	Description	Roll Size (feet)
3"	Solid	125, 5,300
	Perforated	125, 5,300
	Perforated with filter	125, 5,300
4"	Solid	20, 100, 250
	Perforated – small coil	100, 250
	Perforated with Filter – small coil	100, 250
	Perforated – maxi coil	4,000
	Perforated with Filter – maxi coil	3,800
	Heavy Duty 320kPa (S, PF)	250, 4000
	Heavy Duty 320kPa (PF)	250, 4000
6"	Solid	20, 100, 350, 800
	Perforated	20, 100, 350, 800, 1400
	Perforated with Filter	20, 100, 350, 800, 1400
	Heavy Duty 320kPa (S, PF)	Special Order
	Heavy Duty 320kPa (Filter)	Special Order

ONTAROAGRA

Sizing Chart Continued

8"	Solid	20, 100, 350, 800
	Perforated	20, 100, 350, 800
	Perforated with Filter	20, 100, 350, 800
	Flexible Doublewall – Non Perf	825'
	Flexible Doublewall – Perf	825'
	Flexible Doublewall - with Sock	825'
	Flexible Doublewall – Fine Cut	825'
10"	Solid	20, 100, 600
	Perforated	20, 100, 600
	Perforated with Filter	20, 100, 600
12"	Solid	20, 100, 330
	Perforated	20, 100, 330
	Perforated with Filter	20, 100, 330
	Flexible Doublewall – Non Perf	320 ft
	Flexible Doublewall – Perf	320 ft
	Flexible Doublewall - with Sock	320 ft
	Flexible Doublewall – Fine Cut	320 ft
15"	Solid	150 ft
	Fine Cut	150 ft
	Flexible Doublewall – Non Perf	190 ft
	Flexible Doublewall – Perf	190 ft
	Flexible Doublewall - with Sock	190 ft
	Flexible Doublewall – Fine Cut	190 ft